

# Product Specifications

## FlashCheck Digital Lollipop Min/Max Thermometer

<b>Measurement Range</b>	-58°F to 392°F (-50°C to 200°C)
<b>Operating Range</b>	32°F to 122°F (0°C to 50°C)
<b>Accuracy</b>	±1°F (-4°F to 302°F), ±0.5°C (-20°C to 150°C) or ±1% whichever is greatest
<b>Sensor</b>	Thermistor
<b>Display Resolution</b>	0.1°F/ °C
<b>Display Reading Update</b>	1 second
<b>Display Window Size</b>	.77 in W x .37 in H (19.5 mm W x 9.5 mm H)
<b>Calibration</b>	N.I.S.T. Calibration
<b>Battery</b>	Button Cell Alkaline
<b>Body Casing</b>	ABS plastic
<b>Probe Dimensions</b>	7.87 in. (L) x 0.14 in. (Dia) 200 mm (L) x 3.56 mm (Dia)
<b>Weight</b>	1.25 oz. (35.4 gm)
<b>Waterproof Rating</b>	IP67
<b>Certification</b>	CE Mark, RoHS



### Model 11047

- °F/°C selectable
- 200 mm (~8") Sharp Tip probe
- Min/Max memory stores lowest/highest readings until reset
- Probe cover with pocket clip on back
- Waterproof housing, IP67 rated

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system

SS 11047 17A1

